

# **VLS Desktop Series**

## Laser Technology on Your Desktop

The VLS 2.30 and 3.50 desktop lasers are the easiest ways to get started with laser technology. Roughly the size of a printer, a VLS desktop laser packs sophisticated laser processing capabilities into an attractive, durable package. An optional computer-controlled air cleaner cart is available that allows a VLS desktop laser to be used without a dedicated exhaust system, making installation and operation even simpler. The ease of use and small footprint of the VLS desktop laser makes it easy to fit laser technology into your business, whatever it might be.



### **Laser Technology Benefits**

- **Software Controlled -** The laser can be controlled by any software with a print function.
- Multi-Material Process an endless number of materials available today and in the future.
- **Multi-Process -** Cut, engrave, mark, and produce photo images in one step.
- Non Contact Modify material without applying any physical force.
- On Demand Produce everything you need in real time, without waiting for hard tooling.

### **Uniquely Universal Features**

#### ULR Laser Sources

Universal's patented air-cooled free-space gas slab lasers produce an excellent quality beam with even power distribution and good near- and far-field characteristics, making them ideal for laser material processing.

#### High Power Density Focusing Optics<sup>™</sup>

High Power Density Focusing Optics (HPDFO) allow the laser beam to be focused to a much smaller spot, making it possible to engrave smaller text and produce sharper images at tighter tolerances.

#### Laser Interface+™

This materials-based driver automatically determines the optimum processing settings for your target material. Just select the material type, enter in the material thickness, and start the laser system.

#### 1-Touch Laser Photo™

1-Touch Laser Photo is a proprietary software package that makes it quick and easy to produce photographic images on nearly any material.

# **System Specifications**

	VLS2.30	VLS3.50
Work Surface Area	<b>16 x 12 in</b> (406 x 305 mm)	<b>24 x 12 in</b> (610 x 305 mm)
Maximum Part Size <sup>2</sup>	<b>18.75 x 14.6 x 4 in</b> (476 x 370 x 102 mm)	<b>26.75</b> x <b>14.6</b> x <b>4 in</b> (679 x 370 x 102 mm)
Dimensions <sup>3</sup>	<b>26 x 14 x 25 in</b> (660 x 356 x 635 mm)	<b>34 x 14 x 25 in</b> (864 x 356 x 635 mm)
Rotary Capacity	Max Diameter 5 in (127 mm) with 1.5 in (38.1 mm) lens Min Diameter 1 in (25.4 mm) with 2 in (50.8 mm) lens	
Motorized Z Axis Lifting Capacity	<b>20 lbs</b> (9 kg)	
Available Focus Lenses	<b>1.5</b> in (38 mm) <b>2.0</b> in (51 mm) *standard	
Laser Platform Interface Panel	Five button keypad	
Operating System Compatibility	Requires a dedicated PC to operate.  Compatible with Windows XP/Vista/7 – 32/64 bit	
PC Connection	USB 2.0	
Cabinet Style	Desktop	
Optics Protection	Plumbed for compressed-air-based optics protection	
Laser Options	10, 25, 30 Watts	10, 25, 30, 40, 50 Watts
Approximate Weight <sup>3</sup>	70 lbs (32 kg)	95 lbs (43 kg)
Power Requirements	110V/10A; 220V-240V/5A	
Exhaust Connection	One 3 in (76 mm) port 150 CFM @ 6 in static pressure (255 m³/hr at 1.5 kPa)	One 3 in (76 mm) port 250 CFM @ 6 in static pressure (425 m³/hr at 1.5 kPa)

#### **USA**

7845 E. Paradise Lane Scottsdale, AZ 85260

+1 480-483-1214 moreinfo@ulsinc.com

#### Japan

The Yokohama Landmark Tower 15th Fl. 2-2-1-1 Minato Mirai Nishi-ku Yokohama-shi Kanagawa-ken 220-8115 JAPAN

+81 45-224-2270 japansales@ulsinc.com

#### **Europe**

Lerchenfelder Gürtel 43 1160 Vienna, Austria

+43 1-402-22-50 eurosales@ulsinc.com



Learn more at ulsinc.com



CDRH Class 1 safety enclosure for CO2 laser  $^{4}\!.$  Class 3R for red laser pointer.

- <sup>1</sup> Work area varies by speeds and throughput
- <sup>2</sup> Maximum part size defined as used with 1.5 lens
- <sup>3</sup> Does not include optional cart
- <sup>4</sup> CDRH Class 1 laser safety enclosure provides for safe operation without the need for an interlocked room or protective eyewear.

WARNING: UNIVERSAL LASER SYSTEMS PRODUCTS ARE NOT DESIGNED, TESTED, INTENDED OR AUTHORIZED FOR USE IN ANY MEDICAL APPLICATIONS, SURGICAL APPLICATIONS, MEDICAL DEVICE MANUFACTURING, OR ANY SIMILAR PROCEDURE OR PROCESS REQUIRING APPROVAL, TESTING, OR CERTIFICATION BY THE UNITED STATES FOOD AND DRUG ADMINISTRATION OR OTHER SIMILAR GOVERNMENTAL ENTITIES. FOR FURTHER INFORMATION REGARDING THIS WARNING CONTACT UNIVERSAL LASER SYSTEMS OR VISIT WWW.ULSINC.COM.

Manufactured and protected under one or more U.S. Patents: 5,661,746; 5,754,575; 5,867,517; 5,881,087; 5,894,493; 5,901,167; 5,982,803; 6,181,719; 6,313,433; 6,342,687; 6,423,925; 6,424,670; 6,983,001; 7,060,934; D517,474. Other U.S. and international patents pending.

©2011 Universal Laser Systems, Inc. All rights reserved. Universal Laser Systems logo and name are registered trademarks, and Rapid Reconfiguration, Laser Interface+, 1-Touch Laser Photo, SuperSpeed and High Power Density Focusing Optics (HPDFO) are trademarks of Universal Laser Systems, Inc. All other company and product names are trademarks or registered trademarks of their respective companies.

MC038-110411

CPT REV 0112